



MTQ-1 Series MATV Tap

Features:

- 1 way MATV tap 5-1000MHz
- Available tap value: 6, 9, 12, 16, 20, 24, 30 (dB)
- RoHS conform



Specification:

P/N	Tap Value (dB)	Tap Loss	Insertion Loss In-Out (Max. dB)		Return Loss In/Out/Tap (Min. dB)				Isolation Out-Tap/Tap-Tap (Min. dB)			
			5	47	5	47	470	750	5	47	470	750
			-	-	-	-	-	-	-	-	-	-
		1000	47	1000	47	470	750	1000	47	470	750	1000
MHz												
MTQ - 106	6dB	6±1.2	2.2	3.0	17/20/19	19/20/20	22/20/21	21/21/20	25	25	23	22
MTQ - 109	9dB	9±1.5	1.6	2.2	19/19/18	20/20/20	21/20/21	20/21/20	29	27	26	25
MTQ - 112	12dB	12±1.5	2.0	2.2	20/22/20	20/22/20	20/21/21	16/20/18	30	30	28	25
MTQ - 116	16dB	16±1.5	1.0	1.5	33/20/23	30/21/20	26/22/21	24/19/22	33	30	26	24
MTQ - 120	20dB	20±1.5	0.8	1.5	22/20/21	20/20/20	20/20/20	16/20/19	38	31	27	25
MTQ - 124	24dB	24±1.5	1.8	1.8	20/20/20	20/20/20	20/20/20	20/20/20	45	37	31	30
MTQ - 130	30dB	30±1.5	1.5	1.5	20/20/20	20/20/20	20/20/20	20/20/20	60	45	40	35