



MTQ-4 Series MATV Tap

Features:

- 4 way MATV tap 5-1000MHz
- Available tap value: 10, 12, 16, 20, 24 (dB)
- RoHS conform



Specification:

P/N	Tap Value (dB)	Tap Loss	Insertion Loss In-Out (Max. dB)		Return Loss In/Out/Tap (Min. dB)				Isolation Out-Tap/Tap-Tap (Min. dB)			
			5	47	5	47	750	1000	5	47	470	750
			-	-	-	-	-	-	-	-	-	-
		1000	47	1000	47	470	750	1000	47	470	750	1000
MHz												
MTQ - 410	10dB	10±1.5	5.5	4.4	16/16/16	19/18/18	19/18/18	17/16/16	30/20	21/25	25/24	23/21
MTQ - 412	12dB	12±1.5	3.7	4.1	18/15/18	19/20/19	20/18/18	19/18/18	27/27	20/25	28/25	25/25
MTQ - 416	16dB	16±1.5	1.5	2.6	15/15/15	16/18/16	20/20/20	18/18/18	29/28	35/30	35/30	31/28
MTQ - 420	20dB	20±1.5	1.0	1.5	21/15/17	17/20/19	20/20/20	18/18/18	37/23	33/27	30/25	28/21
MTQ - 424	24dB	24±1.5	1.0	1.3	18/16/18	20/20/20	20/19/20	18/18/18	49/20	38/27	37/28	35/28