



HORMAN COMPANY

P. O. BOX 34-141 TAIPEI
7F, NO.33 FUHSING N. ROAD, TAIPEI, TAIWAN.

TEL : 886-2-2752-7198
FAX : 886-2-2772-6108
http : //www.horman.com.tw
E-mail : info@horman.com.tw

MTQ-6 Series MATV Tap

Features:

- 6 way MATV tap 5-1000MHz
- Available tap value: 16, 20, 24 (dB)
- RoHS conform



Specification:

P/N	Tap Value (dB)	Tap Loss	Insertion Loss In-Out (Max. dB)		Return Loss In/Out/Tap (Min. dB)				Isolation Out-Tap/Tap-Tap (Min. dB)			
			5	47	5	47	750	5	47	470	750	
			-	-	-	-	-	-	-	-	-	-
			1000	47	47	470	750	1000	47	470	750	1000
MHz												
MTQ - 616	16dB	16±1.5	2.5	3.0	22/22/22	21/21/21	16/16/16	16/16/16	25/25	25/25	25/25	25/25
MTQ - 620	20dB	20±1.5	1.5	2.2	22/21/16	22/21/16	22/21/16	22/21/16	33/30	30/30	25/25	25/25
MTQ - 624	24dB	24±1.5	1.0	1.5	22/21/16	2/21/16	22/21/16	22/21/16	40/30	35/30	30/25	30/25