



HORMAN COMPANY

P. O. BOX 34-141 TAIPEI

7F, NO.33 FUHSING N. ROAD, TAIPEI, TAIWAN.

TEL : 886-2-2752-7198

FAX : 886-2-2772-6108

http : //www.horman.com.tw

E-mail : info@horman.com.tw

MTQ-8 Series MATV Tap

Features:

- 8 way MATV tap 5-1000MHz
- Available tap value: 16, 20, 24, 28 (dB)
- RoHS conform



Specification:

P/N	Tap Value (dB)	Tap Loss	Insertion Loss In-Out (Max. dB)		Return Loss In/Out/Tap (Min. dB)				Isolation Out-Tap/Tap-Tap (Min. dB)			
			5	47	5	47	750	5	47	470	750	
		5	5	47	5	47	470	750	5	47	470	750
		-	-	-	-	-	-	-	-	-	-	-
		1000	47	1000	47	470	750	1000	47	470	750	1000
MHz												
MTQ - 816	16dB	16±1.5	3.2	4.2	18/18/18	20/20/20	16/16/16	16/16/16	28/30	25/25	22/25	22/25
MTQ - 820	20dB	20±1.5	1.5	2.2	18/18/18	20/20/20	16/16/16	16/16/16	33/30	30/30	25/25	25/25
MTQ - 824	24dB	24±1.5	1.0	1.5	18/18/18	20/20/20	16/16/16	16/16/16	40/30	35/30	30/30	30/30
MTQ - 828	28dB	28±1.5	0.8	1.5	20/20/20	20/20/20	16/16/16	16/16/16	52/30	42/30	42/30	42/30