



HORMAN COMPANY

P. O. BOX 34-141 TAIPEI

7F, NO.33 FUHSING N. ROAD, TAIPEI, TAIWAN.

TEL : 886-2-2752-7198

FAX : 886-2-2772-6108

http://www.horman.com.tw

E-mail : info@horman.com.tw

MTQS-4 Series MATV Tap



Features:

- 4 way MATV tap 5-1000MHz
- Available tap value: 12, 16, 20, 24, 30 (dB)
- RoHS conform

Specification:

P/N	Tap Value (dB)	Tap Loss	Insertion Loss In-Out (Max. dB)		Return Loss In/Out/Tap (Min. dB)				Isolation Out-Tap/Tap-Tap (Min. dB)			
			5	47	5	47	470	750	5	47	470	750
			-	-	-	-	-	-	-	-	-	-
		1000	47	1000	47	470	750	1000	47	470	750	1000
MHz												
MTQS - 412	12dB	12±1.5	3.2	4.5	18/18/18	22/22/22	17/17/17	17/17/17	27/28	25/28	22/25	22/25
MTQS - 416	16dB	16±1.5	2.0	2.5	18/18/18	22/22/22	17/17/17	17/17/17	26/30	26/28	25/25	25/25
MTQS - 420	20dB	20±1.5	1.0	1.5	18/18/18	22/22/22	17/17/17	17/17/17	35/30	32/28	25/25	25/25
MTQS - 424	24dB	24±1.5	0.8	1.0	20/20/20	20/20/20	17/17/17	17/17/17	45/30	35/28	30/25	30/25
MTQS - 430	30dB	30±1.5	0.8	1.0	20/20/20	20/20/20	17/17/17	17/17/17	48/30	40/30	35/25	35/25